

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claim 1 (Canceled)

Claim 2 (Previously presented): A multi-channel fiber optic cable connector for connecting the terminal ends of two multi-channel fiber optic cables having termini of respective ones of multiple optical fibers included within said cables, the connector comprising:

5 translating termini having terminal ends of which extend out of the forward end of an insert cap to prevent mud or debris from becoming lodged within the bores of the insert cap and within alignment sleeves which are contained within the insert cap;

10 a first housing having a first connector face, a first insert cap tower and two first insert cap tangs which extend forward of said first connector face, wherein said two first tangs and said first insert cap tower are spaced apart to extend forward of said first connector face in a keyed arrangement for reciprocally engaging a second housing having a second insert cap tower with two second tangs, said two first tangs fitting adjacent to the second insert cap tower, said first insert cap tower fitting adjacent to the second insert cap tower and the second tangs, and said first connector face fitting against a second forward surface of the second insert cap tower;

15 said first insert cap tower having two interior passages which define first plug body cavities within which are disposed respective ones of a first pair of said termini; and

said first connector face having a pair of interior passages which define two first connector face cavities which are disposed between said first insert cap tower and said two first tangs, from which respective ones of a second pair of said termini extend.

5 Claim 3 (Previously presented): The multi-channel fiber optic cable connector of Claim 2, wherein said two first plug body cavities are aligned with two second connector face cavities which are disposed on a second connector face for receiving respective ones of a third pair of two of said termini therebetween, and said first connector face cavities are aligned with two second plug body cavities of the second insert cap tower for receiving a fourth respective pair of said termini therebetween.

Claim 4 (Original): The multi-channel fiber optic cable connector of Claim 3, wherein said first insert cap, said first connector face and said two first tangs are identically arranged to the second insert cap, the second connector face and the second tangs to provide a hermaphroditic fiber optic cable connector.

Claim 5 (Currently amended): The multi-channel fiber optic cable connector of Claim 4, further comprising

said first housing ~~have~~ having two spaced apart sets of exterior screw threads;

5 a first coupling sleeve extending around said first housing, said first coupling sleeve having at least one set of interior screw threads for threadingly securing said first coupling sleeve to said first housing in first and second positions;

wherein when disposed in said first position, said first coupling sleeve is secured to said first housing in a rearward position relative to said first housing to dispose said first connector in a male mode; and

10 wherein when disposed in said second position, said first coupling sleeve is secured to said first housing in a forward position relative to said first housing to dispose said first connector in a female mode, such that when in the forward position said first coupling sleeve is rotatable relative to said first housing for threadingly engaging the second housing to secure said first housing to the second housing with mating termini aligned for transmitting light signals therebetween.

Claim 6 (Original): The multi-channel fiber optic cable connector of Claim 5, further comprising a pin which extends from said first coupling sleeve into said first housing to non-rotatably secure said first coupling sleeve to said first housing in said first position, wherein said connector is disposed in said male mode.

Claim 7 (Currently amended): The multi-channel fiber optic cable connector of Claim 2, further comprising

said first housing ~~have~~ having two spaced apart sets of exterior screw threads;

5 a first coupling sleeve extending around said first housing, said first coupling sleeve having at least one set of interior screw threads for threadingly securing said first coupling sleeve to said first housing in first and second positions;

wherein when disposed in said first position, said first coupling sleeve is secured to said first housing in a rearward position relative to said first housing to dispose said first connector in a male mode; and

10 wherein when disposed in said second position, said first coupling sleeve is secured to said first housing in a forward position relative to said first housing to dispose said connector in a female mode, such that, when in the forward position, said first coupling sleeve is rotatable relative to said first housing for threadingly engaging the second housing to secure said first housing to the second housing with mating termini aligned for transmitting light signals therebetween.

Claim 8 (Previously presented): A multi-channel fiber optic cable connector for connecting the terminal ends of two multi-channel fiber optic cables having termini of respective ones of multiple optical fibers included within said cables, the connector comprising:

5 translating termini having terminal ends of which extend out of the forward end of an insert cap to prevent mud or debris from becoming lodged within the bores of the insert cap and within alignment sleeves which are contained within the insert cap;

a housing having an insert body with a plurality of interior passages disposed therein for receiving respective ones of the termini of the optical fibers of one of said cables;

10 at least one mating plane for aligning with a mating plane of a second connector for transmitting light signals therebetween;

a plurality of shoulders disposed to extend substantially transverse to the longitudinal axes of said passages for retaining said termini within said passages;

15 a plurality of inwardly extending protuberances which extend inwardly within respective ones of said interior passages, each of said interior passages having one of said shoulders and one of said protuberances, and wherein said shoulders are spaced apart from respective ones of said protuberances and said mating plane, and said protuberances are distally disposed from said mating plane;

20 said protuberances fitting around respective ones of said termini, to gimbal said termini within respective ones of said interior passages, wherein said terminal ends of said termini may angularly move transverse to respective ones of said longitudinal axes thereof, pivoting about said protuberances;

a plurality of floating collars, each of which extends around a respective one of said termini with a clearance fit between said respective ones of said floating collars and said termini such that said floating collars are free to move parallel to longitudinal axes of said respective termini;

25 first seal elements disposed within respective ones of first seal glands, and sealingly engaging between said respective termini and said floating collars;

said floating collars having seal faces which extend parallel to said longitudinal axes of said respective termini, spaced apart from respective ones of said interior passages of said housing to define second seal glands therebetween;

30 second seal elements disposed in said second seal glands, extending around respective ones of said longitudinal axes of said respective termini, and sealingly engaging between respective ones of said seal faces and said interior passages when said termini are angularly displaced about said protuberances;

biasing means to energize said second seal elements;

35 continuous ceramic sleeves having interior bores which are of a slightly wider cross-section than said termini, providing clearance fits between said continuous ceramic sleeves and said termini over lengths which extend parallel to respective ones of said longitudinal axes of said termini; and

40 wherein mating ones of said termini fit within opposite ends of respective ones of said continuous ceramic sleeves to align said terminal ends of said mating ones of said termini for transmitting light signals therebetween.

Claim 9 (Currently amended): The multi-channel fiber optic cable connector of Claim 8, wherein two of said plurality of interior passages define two first plug body cavities and another two of said plurality of interior passages define two first connector face cavities, and wherein said two first plug body cavities are aligned with two second connector face cavities of said second connector

- 5 for receiving two of said termini therebetween, and said two first connector face cavities are aligned with two second plug body cavities of said second connector for receiving a second respective two of said termini therebetween.

- 5 Claim10 (Currently amended): The multi-channel fiber optic cable connector of Claim 9, wherein said insert body includes a connector face and a plurality of tangs, and wherein a second connector includes a second insert cap and a second insert body having a second connector face and a plurality of second tangs, and wherein said insert cap, said connector face and said tangs are identically arranged to said second insert cap, said second connector face and said second tangs to provide a hermaphroditic fiber optic cable connector.

- 5 Claim 11 (Currently amended): The multi-channel fiber optic cable connector of Claim 10, further comprising:  
said housing ~~have~~ having two spaced apart sets of exterior screw threads;  
a coupling sleeve extending around said housing, said coupling sleeve having at least one  
5 set of interior screw threads for threadingly securing said coupling sleeve to said housing in first and second positions;  
wherein when disposed in said first position, said coupling sleeve is secured to said housing in rearward position relative to said housing to dispose said connector in a male mode; and  
10 wherein when disposed in said second position, said coupling sleeve is secured to said housing in a forward position relative to said housing to dispose said connector in a female mode, such that, when in the forward position, said coupling sleeve is rotatable relative to said housing for threadingly engaging the second housing to secure said housing to said second housing with mating termini aligned for transmitting light signals therebetween.

Claim12 (Original): The multi-channel fiber optic cable connector of Claim 11, further comprising a pin which extends from said coupling sleeve into said housing to non-rotatably secure said coupling sleeve to said housing in said first position, wherein said connector is secured in said male mode.

Claim 13 (Currently amended): The multi-channel fiber optic cable connector of ~~Claim 9~~ Claim 10, wherein said plug body cavities, said connector face cavities and said tangs are identically arranged to said second plug body cavities, said second connector face cavities and said second tangs to provide a hermaphroditic fiber optic cable connector.

Claim14 (Currently amended): The multi-channel fiber optic cable connector of Claim 8, further comprising  
said housing ~~have~~ having two spaced apart sets of exterior screw threads;

5 a coupling sleeve extending around said housing, said coupling sleeve having at least one set of interior screw threads for threadingly securing said coupling sleeve to said housing in first and second positions;

wherein when disposed in said first position, said coupling sleeve is secured to said housing in rearward position relative to said housing to dispose said connector in a male mode; and

10 wherein when disposed in said second position, said coupling sleeve is secured to said housing in a forward position relative to said housing to dispose said connector in a female mode, such that said coupling sleeve is rotatable relative to said housing for threadingly engaging the second housing to secure said housing to said second housing with mating termini aligned for transmitting light signals therebetween.

Claim15 (Original): The multi-channel fiber optic cable connector of Claim 14, further comprising a pin which extends from said coupling sleeve into said housing to non-rotatably secure said coupling sleeve to said housing in said first position, wherein said connector is secured in said male mode.

Claim 16 (Previously presented): A multi-channel fiber optic cable connector for connecting the terminal ends of two multi-channel fiber optic cables having termini of respective ones of multiple optical fibers included within said cables, the connector comprising:

5 translating termini having terminal ends of which extend out of the forward end of an insert cap to prevent mud or debris from becoming lodged within the bores of the insert cap and within alignment sleeves which are contained within the insert cap;

10 a housing having an insert body with a plurality of interior passages disposed therein for receiving respective ones of the termini of optical fibers of one of said cables, at least one mating plane for aligning with a second and at least one mating plane of a second housing for transmitting light signals therebetween, and a plurality of shoulders disposed to extend substantially transverse to the longitudinal axes of said passages, and a plurality of inwardly extending protuberances which extend inwardly within respective ones of said interior passages, each of said interior passages having one of said shoulders and one of said passages, and wherein said shoulders are spaced apart from respective ones of said protuberances and said mating plane, and said protuberances are distally  
15 disposed from said mating plane;

said protuberances fitting around respective ones of said termini, to gimbal said termini within respective ones of said interior passages, wherein said terminal ends of said termini may angularly misalign to respective ones of said longitudinal axes thereof, pivoting about said protuberances;

20 a plurality of floating collars, each of which extends around a respective one of said termini with a clearance fit between said respective ones of said floating collars and said termini such that said floating collars are free to move parallel to longitudinal axes of said respective termini;

first seal elements disposed within respective ones of first seal glands, and sealingly engaging between said respective termini and said floating collars;

25 said floating collars having seal faces which extend parallel to said longitudinal axes of said

respective termini, spaced apart from respective ones of said interior passages of said housing to define second seal glands therebetween;

30 second seal elements disposed in said second seal glands, extending around respective ones of said longitudinal axes of said respective termini, and sealingly engaging between respective ones of said seal faces and said interior passages when said termini are angularly displaced about said protuberances;

biasing means to energize the second seal elements;

35 continuous ceramic sleeves having interior bores which are of a slightly wider cross-section than said termini, providing clearance fits between said continuous ceramic sleeves and said termini over lengths which extend parallel to respective ones of said longitudinal axes of said termini;

wherein mating ones of said termini fit within opposite ends of respective ones of said continuous ceramic sleeves to align said terminal ends of said mating ones of said termini for transmitting light signals therebetween;

40 said housing having a forwardly extending insert cap, a connector face and two forwardly extending tangs, said insert cap extending forward of said connector face, and wherein said two tangs and said insert cap are spaced apart in a keyed arrangement for receiving a second main body having a second insert cap and two second tangs, said tangs fitting adjacent to the second insert cap, said insert cap fitting adjacent to the second insert cap and the second tangs and said connector face fitting against a forward face of the second insert cap;

45 said insert cap having two of said interior passages of said housing which define insert cap cavities within which are disposed respective ones of said termini; and

said connector face having a second two of said interior passages of said housing which define two connector face cavities which are disposed between said insert cap and said tangs, from which respective ones of said termini extend.

5 Claim 17 (Currently amended): The multi-channel fiber optic cable connector of Claim 16, wherein two of said interior passages are disposed in a first insert cap to define two plug body cavities within which are disposed two respective ones of said termini, and said two plug body cavities are aligned with two second connector face cavities of a second connector face of said second connector for receiving two of said termini therebetween, and said connector face cavities are aligned with two second plug body cavities of said second insert cap for receiving a second respective two of said termini therebetween.

Claim 18 (Original): The multi-channel fiber optic cable connector of Claim 16, wherein said insert cap, said connector face and said tangs are identically arranged to said second insert cap, said second connector and said second tangs to provide a hermaphroditic fiber optic cable connector.

Claim 19 (Currently amended): The multi-channel fiber optic cable connector of Claim 16, further comprising

said housing ~~have~~ having two spaced apart sets of exterior screw threads;

5 a coupling sleeve extending around said housing, said coupling sleeve having at least one set of interior screw threads for threadingly securing said coupling sleeve to said housing in first and second positions;

wherein when disposed in said first position, said coupling sleeve is secured to said housing in rearward position relative to said housing to dispose said connector in a male mode; and

10 wherein when disposed in said second position, said coupling sleeve is secured to said housing in a forward position relative to said housing to dispose said connector in a female mode, such that, when in the forward position, said coupling sleeve is rotatable relative to said housing for threadingly engaging the second housing to secure said housing to said second housing with mating termini aligned for transmitting light signals therebetween.

Claim 20 (Original): The multi-channel fiber optic cable connector of Claim 19, further comprising a pin which extends from said coupling sleeve into said housing to non-rotatably secure said coupling sleeve to said housing in said first position, wherein said connector is secured in said male mode.

Claim 21 (Previously presented): A method for joining two multi-channel fiber optic cables for transmitting light signals therebetween, comprising the steps of:

5 providing first and second connector housings, each having a plurality of interior passages for receiving respective ones of termini of the optical fiber of the fiber optic cables, with the interior passages of respective ones of the first and second connector housings aligned for registering with respective ones of the interior passages of the other of the first and second connector housings;

providing translating termini having terminal ends of which extend out of the forward end of an insert cap to prevent mud or debris from becoming lodged within the bores of the insert cap and within alignment sleeves which are contained within the insert cap;

10 mounting a plurality of floating collars around the termini, each of the floating collars mounted to a respective one of the termini, slidable in a longitudinal direction relative to the respective termini;

disposing first seal elements between the floating collars and the respective ones of the termini, sealingly engaging therebetween;

15 disposing second seal elements between the floating collars and the interior passage of respective ones of the first and second connector housings;

20 biasing the floating collars into forward positions, wherein the forward ends of the floating collars are pressed against the first seal elements to energize the first seal elements to sealingly engage between the floating collars and the interior surfaces of respective ones of the first and second connector housings;

25 mounting the termini within respective ones of the interior passages of the first and second connector housings, with the termini angularly moveable with respect to a gimbal point which is distally disposed from terminal ends of the respective ones of the termini, and the second seal element sealingly engaging between the floating collars and the interior passages of the housing as the termini are angularly moved within the respective ones of the interior passages;

slidably disposing respective ones of continuous rigid sleeves within respective ones of the interior passages of the first and second connector housings, with respective ones of the termini disposed in each of the continuous rigid sleeves with a slidably engaging clearing therebetween; and mating the first connector housing with the second connector housing to slidably engage the termini of respective ones of the first and second connector housings within corresponding ones of the continuous sleeves to align the termini of the first and second connectors for transmitting light therebetween.

Claim 22 (Original): The method of Claim 21, further comprising:  
providing each of the first and second connector housings with respective ones of two coupling sleeves which extend around respective ones of the first and second connector housings and are threadingly securable thereto in at least first and second positions;  
threadingly securing a first one of the two coupling sleeves to the first connector housing in the first position, wherein the first one of the two coupling sleeves is disposed rearward of a forward end of the first connector housing to dispose the first connector housing and the first one of the two coupling sleeves in a male mode; and then,  
threadingly securing a second one of the two coupling sleeves to the second connector housing in the second position, wherein the second one of the two coupling sleeves is disposed forward relative to the first position, to dispose the second connector housing and the second one of the two coupling sleeves in a female mode.

Claim 23 (Original): The method of Claim 22, further comprising the step of latching the first one of the two coupling sleeves into the first position relative to the forward end of the first connector housing, to latch the first connector housing and the first one of the two coupling sleeves into the male mode.